















ZENER DIODES

P _{tot} (mW)	Zener Voltage Range V _Z (V)	Zener Voltage Tolerances					
		5 %	2 %	DO-214AC (SMA)	DO-214AA (SMB)	MicroMELF (Glass)	QuadroMELF SOD-80 (Glass)
Characteristics				Surface-Mount			
200	2.4 to 51	C					
200	2.4 to 75	C	B				
200	2.02 to 36.87						
300	2.7 to 51	C	B				
300	2.4 to 75	C	B				
300	2.7 to 51	C	B				
300	3.0 to 75	B	C				
350	2.4 to 6.2	Std					
350	2.4 to 43	Std					
410	2.4 to 75	C	B				
500	2.4 to 43	Std					
500	3.0 to 75	Std					
500	13 to 27		Std				
500	2.4 to 75	Std					TZQ5221B-5267B
500	1.8 to 43	Std					TZS4678-4717 ⁽¹⁾
500	2.4 to 75	C	B			BZM55 Series	BZT55 Series
500	2.4 to 36						
500	2.4 to 56						
800	3.6 to 200	Std					
1000	3.3 to 100	Std		SML4738A to SML4764A			
1000	3.9 to 100	Std					
1000	100 to 200	Std					
1250	3.3 to 100	Std		BZG05C Series			
1300	2.7 to 100	C	B				
1300	3.9 to 100	Std					
1500	3.9 to 36	Std					
1500	5.6 to 43	B					
1500	100 to 200	Std					
1500	9.1 to 68	B			SMZJ3788B-3809B		
1500	5.6 to 68	B		SMAZ5919B-5945B			
3000	10 to 270	Std		BZG03C Series			
3000	5.6 to 68	B			SMBZ5919B-5945B		
3250	6.2 to 300	C					
6000	6.8 to 270	C					
Dimensions							
				DO-214AC (SMA)	DO-214AA (SMB)	MicroMELF	QuadroMELF

(1) Specified at very low Zener current



ZENER DIODES

P _{tot} (mW)	Zener Voltage Range V _Z (V)	Zener Voltage Tolerances					
		5 %	2 %	MiniMELF SOD-80 (Glass)	MELF DO-213AB (Glass)	MELF DO-213AB (Plastic)	DO-35 (Glass)
Characteristics				Surface-Mount		Leaded	
200	2.4 to 51	C					
200	2.4 to 75	C	B				
200	2.02 to 36.87						
300	2.7 to 51	C	B				
300	2.4 to 75	C	B				
300	2.7 to 51	C	B				
300	3.0 to 75	B	C				
350	2.4 to 6.2	Std					
350	2.4 to 43	Std					
410	2.4 to 75	C	B				
500	2.4 to 43	Std					
500	3.0 to 75	Std					
500	13 to 27		Std				
500	2.4 to 75	Std		TZM5221B-5267B			1N5221B - 5267B
500	1.8 to 43	Std					
500	2.4 to 75	C	B	TZM* TZM*-M			BZX55 Series
500	2.4 to 36						TZX Series
500	2.4 to 56			TLZ Series			
800	3.6 to 200	Std					
1000	3.3 to 100	Std			ZM4728A-4764A		
1000	3.9 to 100	Std			ZMY Series		
1000	100 to 200	Std				ZGL41 Series	
1250	3.3 to 100	Std					
1300	2.7 to 100	C	B				
1300	3.9 to 100	Std					
1500	3.9 to 36	Std					
1500	5.6 to 43	B					
1500	100 to 200	Std					
1500	9.1 to 68	B					
1500	5.6 to 68	B					
3000	10 to 270	Std					
3000	5.6 to 68	B					
3250	6.2 to 300	C					
6000	6.8 to 270	C					
Dimensions							
				MiniMELF	MELF	DO-213AB Plastic	DO-35