

MINI COAX SERIES CONNECTORS

FOR CABLE SIZES 30AWG : 25AWG : 23AWG

Holland Electronics offers the most complete line of connectors for mini coax available in the industry. Take advantage of our one-piece designs that enable you to terminate your cables in 15 seconds. Our connectors are available for the most popular mini cable sizes ranging from 23-30 AWG center conductors. Designed for all applications in CATV, satellite, home theater, broadcast and satellite radio.

COMPRESSION - 23 AWG : 25 AWG : 30 AWG



SLC-23-F
SLC1855-FP2
SLC1855-FPU
SLC-MINI25U
SLC-179DT-FP (2 PIECE)



SLC-23-BNC
SLC1855-BNCFP
SLC1855-BNCFPU
SLC-BNC-MINI25U
SLC-BNC-179DT (2 PIECE)



SLC-23-RCA
SLC1855-RCAFP
SLC1855-RCAFPU
SLC-RCA-MINI25U
SLC-RCA-179DT (2 PIECE)

Our patented Compression "U" (Universal) Models above can be used on a wider range of cable sizes

CRIMP - 23 AWG



F1855-FP



BNC1855-FP



RCA-1855

RIGHT ANGLE COMPRESSION



SLC1855-90-F



SLC1855-90-BNC



SLC1855-90-RCA

FEMALE BULKHEADS



GF-1855-A



BNCFPFBH



RCAFPFBH

SMA - CRIMP



SMAFP



SMAFP90



SMAFPF

SMB - CRIMP



SMBFP



SMBFP90



SMBFPF

* Other versions available

RELATED PRODUCTS



INSTALLER BAG

Designed to carry all of your connectors, mini cable and tools (see page 76 for more details)



CT-FBR / COMPRESSION TOOL

Terminates F, BNC, RCA as well as speaker wire connectors
(More Connector Tools on page 106)

Applicable Patents - reference: G - See page 111 for patent details

MINI COAX SERIES CONNECTORS

SERIES 23 AWG CABLE

(Nominal Cable OD .159")

COMPRESSION CONNECTORS

For Holland HVS Series : Belden YR46940, 1855A : Commscope 7538 or Similar

MODEL #	DESCRIPTION	PLATING	CLOSURE SIZE
SLC-23-F	F Male / Fixed Pin 1 Piece	Nickel	29.8 mm
SLC1855-FP2	F Male / Fixed Pin / 1 Piece	Nickel	29.8 mm
SLC1855-FPU	F Male / Fixed Pin / 1 Piece / Universal	Nickel	29.8 mm
SLC-23-RCA	RCA Male / Fixed Pin / 1 Piece	Nickel	29.8 mm
SLC1855-RCAFP	RCA Male / Fixed Pin / 1 Piece	Nickel	29.8 mm
SLC1855-RCAFPG	RCA Male / Fixed Pin / 1 Piece	Gold	29.8 mm
SLC1855-RCAFPU	RCA Male / Fixed Pin / 1 Piece / Universal	Nickel	29.8 mm
SLC-23-BNC	BNC Male / Fixed Pin / 1 Piece	Nickel	29.8 mm
SLC1855-BNCFP	BNC Male / Fixed Pin / 1 Piece	Nickel	29.8 mm
SLC1855-BNCFPU	BNC Male / Fixed Pin / 1 Piece / Universal	Nickel	29.8 mm
SLC1855-90-F	90° F Male / Fixed Pin / 1 Piece / Universal	Nickel	29.8 mm
SLC1855-90-RCA	90° RCA Male / Fixed Pin / 1 Piece / Universal	Nickel	29.8 mm
SLC1855-90-BNC	90° BNC Male / Fixed Pin / 1 Piece / Universal	Nickel	29.8 mm

SERIES 23 AWG CABLE

(Nominal Cable OD .159")

CRIMP CONNECTORS

For Holland HVS Series : Belden YR46940, 1855A : Commscope 7538 or Similar

MODEL #	DESCRIPTION	PLATING	HEX SIZE
F1855-FP	F Male / Fixed Pin / 1 Piece	Nickel	.270 in
RCA-1855	RCA Male / Fixed Pin / 1 Piece	Gold	.270 in
BNC1855-FP	BNC Male / Fixed Pin / 1 Piece	Nickel	.270 in
GF-1855-A	F Female / Fixed Pin / 1 Piece	Nickel	.270 in
RCAFPFBH	RCA Female / Fixed Pin / 1 Piece	Nickel	.270 in
BNCFPFBH	BNC Female / Fixed Pin / 1 Piece	Nickel	.270 in
SMAFP	SMA Plug / 1 Piece	Nickel	.270 in
SMAFP90	90° SMA Plug / 1 Piece	Nickel	.270 in
SMAFPF	SMA Jack / 1 Piece	Nickel	.270 in
SMBFP	SMB Plug / 1 Piece	Nickel	.213 in
SMBFP90	90° SMB Plug / 1 Piece	Nickel	.213 in
SMBFPF	SMB Jack / 1 Piece	Nickel	.213 in

SERIES 25 AWG CABLE

(Nominal Cable OD .141")

COMPRESSION CONNECTORS

For Belden 1279R, 1279P, HC2950 or Similar

MODEL #	DESCRIPTION	PLATING	CLOSURE SIZE
SLC-MINI25-U	F Male / Fixed Pin / 1 Piece / Universal	Nickel	29.8 mm
SLC-RCA-MINI25U	RCA Male / Fixed Pin / 1 Piece / Universal	Nickel	29.8 mm
SLC-BNC-MINI25U	BNC Male / Fixed Pin / 1 Piece / Universal	Nickel	29.8 mm

SERIES 30 AWG CABLE

(Nominal Cable OD .110")

COMPRESSION CONNECTORS

For Belden 179DT or Similar

MODEL #	DESCRIPTION	PLATING	CLOSURE SIZE
SLC-179DT-FP	F Male / Fixed Pin / 2 Piece	Nickel	29.8 mm
SLC-RCA-179DT	RCA Male / Fixed Pin / 2 Piece	Nickel	29.8 mm
SLC-BNC-179DT	BNC Male / Fixed Pin / 2 Piece	Nickel	29.8 mm

NOTE: Ask your sales representative for the correct connectors if your cable is not listed here.